

XLS – Universal LED Exit

➤ XLS Basics

- Dual Voltage 120/277
- Universal Mount
- Single or Double face
- 90 Minute NiCad Battery
- Long Life, 1.5 Watt Red or 2.8 Watt Green LED Light Source
- Order in Red or Green

➤ Mounting Details

- Easy snap fit canopy can be used for top or end mounting or knockouts can be used for wall/back mounting.
- Included second face allows the unit to be used as a single or double face exit sign.
- Snap fitting, replaceable chevrons for direction indication.

➤ Battery Details

- Maintenance free, Sealed Nickel Cadmium battery provides a minimum 1 ½ hour emergency operation for Self-Powered signs.
- Low voltage disconnect of the battery prevents deep discharge and maintains good battery life.
- Fully automatic, solid state charger.
- Test switch with LED charge indicator/AC voltage indicator.

➤ Why P2 for LED Exits?

- Always in Stock for Quick Ship
- Complete your relighting project bill of materials, kits, fixtures, indoor, outdoor, exits, with a single PO.

➤ Approvals

- UL924
- Life Safety NFPA 101
- UL Listed for Damp Location

➤ XLS – Universal LED Exit with Battery Backup



Ordering Information

XLS-R = Red Letter, Universal Volt/Mount, LED Exit with Battery Backup
XLS-G = Green Letter, Universal Volt/Mount, LED Exit with Battery Backup